



TNMG 332 Z8

APPLICATION

- Generic grade for steel
- Suitable for fine machining of steels, stainless steel and cast-irons



GRADE Z8

This is a TIN PVD coated carbide insert for fine machining of steels, stainless steel and cast-irons

	STEEL	STAINLESS	CAST IRON	NON FERROUS	S.ALLOYS	HEAT TREATED
GROUP	P30	M30	K30			
Sfm ft/min	427 - 640	246 - 377	394 - 607			
Fn Inch/Z	0.0059 - 0.0157	0.0065 - 0.0142	0.0059 - 0.0157			
ap Inch	0.031 - 0.118	0.031 - 0.118	0.031 - 0.118			

LEGEND

Sfm (Vc)	Surface Feet per Minute
Fn (ipr)	Feed per revolution
Fz (ipt)	Feed per tooth
ap	Depth of cut

FORMULA

$S \text{ (RPM)} = \text{Sfm} * 12 / \pi / D = \text{rev per minute}$
$F \text{ (IPR, inch per revolution)} = S * \text{Fn} = \text{feed per minute}$
$F \text{ (IPM, inch per minute)} = S * Fz * n.\text{flutes} = \text{feed per minute}$
$\text{Sfm} = S * D * \pi / 12$

TURNING CARBIDE INSERT