



SCET 070308 Z2



APPLICATION

- Drilling insert to fit the peripheral pocket of 841 drilling bodies
- Square geometry for machining of steel and stainless-steel

GRADE Z2

This is a MT-CVD coated functionally graded WC-Co carbide within ISO-grade ranges P20-P35 and M15-M30 with SD geometry for machining of steel and stainless-steel

	STEEL	STAINLESS	CAST IRON	NON FERROUS	S.ALLOYS	HEAT TREATED
GROUP	P25	M25	K20		S20	
Sfm ft/min	558 - 787	328 - 459	525 - 738		98 - 230	
Fn Inch/Z	0.003 - 0.007	0.003 - 0.006	0.003 - 0.007		0.003 - 0.005	
ap Inch						

LEGEND

Sfm (Vc)	Surface Feet per Minute
Fn (ipr)	Feed per revolution
Fz (ipt)	Feed per tooth
ap	Depth of cut

FORMULA

$S \text{ (RPM)} = \text{Sfm} * 12 / \pi / D = \text{rev per minute}$
 $F \text{ (IPR, inch per revolution)} = S * F_n = \text{feed per minute}$
 $F \text{ (IPM, inch per minute)} = S * F_z * n.\text{flutes} = \text{feed per minute}$
 $\text{Sfm} = S * D * \pi / 12$

DRILLING CARBIDE INSERT